



Duct Liner Pins

CS-10 Cupped Head Weld Pin

Cupped Head:

Reduces jams and machinery down time while preserving the insulation.

Contact Head:

Oversized head increases the welding surface, resulting in a reduction in misfires and superior strength.



Point:

Forged diamond point for strength and weld consistency.

Shaft:

High tempered shaft for strength and consistency.

Fastener Size	Quantity	Recommended for:
1/2"	5M	1/2" Insulation - All Densities
3/4"	5M	3/4" Insulation - 1-1/2 lb. Densities
1"	5M	1" Insulation - 3 lb. Densities
1-1/8"	3M	1-1/8" Insulation - 4 to 6 lb. Densities
1-1/2"	3M	1-1/2" Insulation - 1-1/2 lb. Densities
2"	3M	2" Insulation - 1-1/2 & 2 lb. Densities

Made in the USA

Limited Product Warranty: GEMCO is not liable for consequential, incidental, or special damages. There are no statutory or implied warranties including the warranties of fitness for a particular purpose and merchantability. There are no warranties other than as set forth below and GEMCO neither assumes nor authorizes any person to assume any liability or other obligation in connection with GEMCO.

GEMCO Weld Pins are warranted to be free from any and all defects in material and workmanship only at the time of shipment from our plant. If material is shown to be defective at time of shipment from our plant, GEMCO will replace or issue credit for the original purchase price.

GEMCO Weld Pins will provide a strong welded connection with most surfaces normally used in duct construction when used in accordance with approved welding equipment.

GEMCO does not guarantee the results from the use of GEMCO WELD PINS because of the extreme differences in surface texture and porosity of available materials and the possibility of structural movement or externally caused damages.